

Steckachsen 2019



Made in Berlin since 1994

	Set 17	Set 17 boost	Set 18	Set 18 boost	Set 19	Set 20	Set 20 boost	Set 21	Set 21 boost	Set 22	Set 23	Set 23 kurz	Set 24	Set 24 boost	Set 25	Set 26	Set 26 boost
Artikelnummer Article	P170000	P17B000	P180000	P18B000	P190000	P200000	P20B000	P210000	P21B000	P220000	P230000	P23K000	P240000	P24B000	P250000	P260000	P26B000
Nachkauf (ohne Schlüssel) reorder (without key)	PNC15ML	PNC15MB	PNC15FR	PNC15FB	PNC15ST	PNC12ML	PNC12MB	PNC15SU	PNC15SB	PNC15SK	PNC12MR	PNC12MRK	PNC12ET	PNC12EB	PNC15MC	PNC12XR	PNC15XB
Position position	front	front	front	front	front	rear	rear	front	front	front	front	front	rear	rear	front	rear	rear
Funktion function	Maxle MTB	Maxle MTB boost	FOX MTB	FOX MTB boost	Stevens K1 fork	Maxle MTB, Trekking, Road/CC	Maxle MTB	Suntour MTB	Suntour MTB boost	Suntour Trekking	Maxle Road/CC	Maxle Road/CC	E-Thru	E-Thru boost	Maxle CC	X-12	X-12 boost
a Durchmesser Diameter	15	15	15	15	15	12	12	15	15	15	12	12	12	12	15	12	12
b Gesamtlänge total length	148	158	146	156	133,2	172	178	140	150	120	125	120	170	175	125	165	170
c Einbaubreite installation width	100	110	100	110	100	142	148	100	110	100	100	100	142	148	100	142	142/148
d Gewindelänge thread length	15	15	15	15	15	20	20	/	/	/	15	15	20	20	15	20	20
Gewinde thread	M15 x 1,5	M15 x 1,5	M14 x 1,5	M14 x 1,5	M14 x 1,5	M12 x 1,75	M12 x 1,75	/	/	/	M12 x 1,5	M12 x 1,5	M12 x 1,5	M12 x 1,5	M15 x 1,5	M12 x 1,0	M12 x 1,0
Gewicht weight	85g	88g	82g	86g	87g	66g	68g	100g	106g	92g	50g	49g	64g	66g	55g	62g	64g
Andruckfläche an Ausfallende contact area on dropout	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 19 mm	ø 22 mm	ø 22 mm	ø 22 mm	ø 19 mm	ø 19 mm

